

WPC VINYL



NEW YORK COLLECTION

7" x 60" x 5/16" | 180mm x 1520mm x 8mm



East Village
MESP-328



Lenox Hill
MESP-329



Tribeca
MESP-326



Central Park
MESP-325



Chelsea
MESP-327

MARQUEE FLOORS
by **TORLYS**

torlys.com

Apr 2021

NEW YORK COLLECTION

Exceptional Performance At An Unbelievable Value

DETAILS

- 5mm thick high density waterproof core
- 20mil (0.5mm) wear layer
- Durable Easy Clean Protect Plus Surface Coating
- FoamPlus™ BLUE attached underlay with Microban® antimicrobial protection and increased sound reduction
- Precision bevel edge
- SureDrop locking system
- Sound rating of IIC: 71 / STC: 62

DIMENSIONS

- Plank: 7" (w) x 60" (l)
180mm x 1520mm
- Thickness: 5/16" / 8mm
- Wear Layer Thickness: 0.5mm / 20mil

WARRANTY

- 15-Year Limited Wear and Structural Warranty for Commercial Use.
- 25-Year Limited Wear Warranty and a Lifetime Structural Warranty for Residential Use.

TECHNICAL SPECIFICATIONS

Test Method Results / Parameters

Total thickness - EN - ISO 24346 (EN 428)	+ 0.15 mm
Wear layer thickness - EN - ISO 24340 (EN 429)	+ 0.03 mm
Size EN - ISO 24342	7" X 60"
Squareness and straightness EN - ISO 24342 / ASTM F 2055	Pass
Slip resistance - DIN 51130 (EN 13893)	R10
Impact Insulation Class - ASTM E 492-09 / ASTM E 989-06	71
Castor Chair suitability - EN 425 (ISO 4918)	Pass
Residual indentation - EN 433 (ISO 24343-1)	0.02 mm / < 0.1 mm
Light fastness - EN - ISO 105-B02	> 6
Resistance to chemicals - EN - ISO 26987 / EN 423	Class 0

Test Method Results / Parameters

Reaction to fire - EN 13501 (ASTM E 648)	Bfl-S1
Classification - ISO 10874 (EN 685)	Domestic: Class 23 Heavy Commercial: Class 32 General Light industrial: Class 41 Moderate
Thermal resistance - EN 12524 (ISO 10456) / EN 12667	0.041 K.m ² /W
Electrical behaviour (EN 1815)	Voltage: 0.5kV
Abrasive resistance - EN 660 - 2	Wear Group: T
Wear layer binder content - ISO 10582	100%
Dimensional stability - EN 434 (EN ISO 23999)	Pass
Phthalate-free (CPSC-CH-C 1001-09.3)	Pass